

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

RT153F Resin

Revision 2

Revision date 2015-05-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RT153F Resin

1.3. Details of the supplier of the safety data sheet

Company ResinTech Limited
Address Horcott, Fairford,
Gloucestershire GL7 4BX
Web www.resintech.co.uk
Telephone +44 (0)1285 712755
Fax +44 (0)1285 712999
Email info@resintech.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC
Xi; R36/38-43 N; R51/53
Symbols: Xi: Irritant. N: Dangerous for the environment.

Main hazards
Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.1.2. Classification - EC 1272/2008
Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms



Signal Word

Warning

Hazard Statement

Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statement: Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement: Response

P302+P352 - IF ON SKIN: Wash with plenty of water/ .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 - Specific treatment (see on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

RT153F Resin

Revision 2

Revision date 2015-05-12

2.2. Label elements

Precautionary Statement: Disposal	P391 - Collect spillage.
	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5		60 - 80%	Xi; R36/38 R43 N; R51/53	
Cyclohexanedimethanol, 1,4-diglycidyl ether		14228-73-0			20 - 40%	Xi; R36/38-43 R52/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5		60 - 80%	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411;	
Cyclohexanedimethanol, 1,4-diglycidyl ether		14228-73-0			20 - 40%	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to eyes and respiratory system. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Bathe the eye with running water for 15 minutes. Irritating to eyes. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. Wash off immediately with plenty of soap and water.
Ingestion	DO NOT INDUCE VOMITING. Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective clothing.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled container.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

RT153F Resin

Revision 2

Revision date 2015-05-12

7.2. Conditions for safe storage, including any incompatibilities

	Keep container tightly closed. Keep in a cool, dry, well ventilated area. Store in correctly labelled containers.
--	---

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
---	--

8.2.2. Individual protection measures	Wear suitable protective clothing.
---------------------------------------	------------------------------------

Eye / face protection	Approved safety goggles.
-----------------------	--------------------------

Skin protection - Handprotection	Wear suitable protective clothing and gloves.
----------------------------------	---

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	= Liquid
Colour	= Colourless
Odour	= Characteristic

9.2. Other information

Benzene Content	= 0
Lead content	= 0
VOC (Volatile organic compounds)	= 0

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

SECTION 12: Ecological information

12.6. Other adverse effects

	May cause long-term adverse effects in the aquatic environment. Toxic to aquatic organisms.
--	---

SECTION 13: Disposal considerations

Disposal methods

	Contact a licensed waste disposal company.
--	--

Disposal of packaging

	After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free).
--	--

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

RT153F Resin

Revision 2

Revision date 2015-05-12

14.1. UN number	
	UN3082
14.2. UN proper shipping name	
	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A)
14.3. Transport hazard class(es)	
ADR/RID	9
Subsidiary risk	-
IMDG	9
Subsidiary risk	-
IATA	9
Subsidiary risk	-
14.4. Packing group	
Packing group	III
14.5. Environmental hazards	
Environmental hazards	Yes
Marine pollutant	Yes
ADR/RID	
Hazard ID	90
Tunnel Category	(E)
IMDG	
EmS Code	F-A S-F
IATA	
Packing Instruction (Cargo)	964
Maximum quantity	450 L
Packing Instruction (Passenger)	964
Maximum quantity	450 L

SECTION 15: Regulatory information**SECTION 16: Other information****Other information**

Revision	This document differs from the previous version in the following areas:. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R36/38 - Irritating to eyes and skin. R43 - May cause sensitisation by skin contact. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

RT153F Resin

Revision 2

Revision date 2015-05-12

Other information	
Maximum content of VOC	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. 0.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.