

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

RT154TH Resin

Revision 8

Revision date 2015-10-22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	RT154TH Resin
--------------	---------------

1.3. Details of the supplier of the safety data sheet


Company	ResinTech Limited
Address	Horcott, Fairford, Gloucestershire GL7 4BX
Web	www.resintech.co.uk
Telephone	+44 (0)1285 712755
Fax	+44 (0)1285 712999
Email	info@resintech.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/38-43 N; R51/53 Symbols: Xi: Irritant. N: Dangerous for the environment.
Main hazards	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P391 - Collect spillage.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to an appropriate waste site or reclaim (in accordance with local/regional/national/international regulation).

RT154TH Resin

Revision 8

Revision date 2015-10-22

SECTION 3: Composition/information on ingredients**3.2. Mixtures****67/548/EEC / 1999/45/EC**

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5		80 - 100%	Xi; R36/38 R43 N; R51/53	
Epoxy resin Bisphenol F		28064-14-4	500-033-5		5 - 10%	Xi; R36/38-43 N; R51/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Bisphenol A-(epichlorhydrin) (reaction product)	603-074-00-8	25068-38-6	500-033-5		80 - 100%	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411;	

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation	May cause irritation to eyes and respiratory system. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Bathe the eye with running water for 15 minutes. Irritating to eyes. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. Wash off immediately with plenty of soap and water.
Ingestion	DO NOT INDUCE VOMITING. Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Wear suitable protective clothing.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Remove mechanically; cover the remainder with wet, absorbent material (e.g. sawdust, chemical binder based on calcium silicate hydrate, sand). After approximately one hour transfer to waste container and do not seal (evolution of CO2!). Sweep up. Transfer to suitable, labelled container.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep container tightly closed. Keep in a cool, dry, well ventilated area. Store in correctly labelled
--	---

RT154TH Resin

Revision 8

Revision date 2015-10-22

7.2. Conditions for safe storage, including any incompatibilities

containers.

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear suitable protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Wear suitable protective clothing and gloves.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Off white
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.6. Other adverse effects

May cause long-term adverse effects in the aquatic environment. Toxic to aquatic organisms.

SECTION 13: Disposal considerations

Disposal methods

Contact a licensed waste disposal company.

Disposal of packaging

After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free).

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN3082

14.2. UN proper shipping name

RT154TH Resin

Revision 8

Revision date 2015-10-22

14.2. UN proper shipping name

	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A)
--	---

14.3. Transport hazard class(es)

ADR/RID	9
Subsidiary risk	-
IMDG	9
Subsidiary risk	-
IATA	9
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

ADR/RID

Hazard ID	90
Tunnel Category	(E)

IMDG

EmS Code	F-A S-F
----------	---------

IATA

Packing Instruction (Cargo)	964
Maximum quantity	450 L
Packing Instruction (Passenger)	964
Maximum quantity	450 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
-------------	--

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 2 - Hazard pictograms. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R36/38 - Irritating to eyes and skin. R43 - May cause sensitisation by skin contact.

RT154TH Resin

Revision 8

Revision date 2015-10-22

Other information

Text of Hazard Statements in Section 3	R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--