

Revised: 1/10/2024

SAFETY DATA SHEET

This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: RT370 PART A (RESIN)
- UFI: KR20-40Q2-X005-UND1
- Product Part Number: RT370 PART A (RESIN)

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Resin

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Resintech Ltd
- Address of Supplier: Unit 1-2 Horcott Industrial Estate
Fairford
Gloucestershire
GL7 4BX
UK
- Telephone: +44 (0)1285 712755
- Responsible Person: Alex Paton
- Email: Info@resintech.co.uk

1.4 Emergency telephone number

- Emergency Telephone: +44 (0)1285712755 (Monday-Friday 8am-4.30pm)
-

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- CLP: Skin Sens. 1, Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2

2.2 Label elements



- Signal Word: Warning
- Contains: Bis-[4-(2,3-epoxipropoxy)phenyl]propane

Hazard statements

- H315 - Causes skin irritation.
 - H317 - May cause an allergic skin reaction.
 - H319 - Causes serious eye irritation.
 - H411 - Toxic to aquatic life with long lasting effects.
-

SECTION 2: Hazards identification (....)**Precautionary statements**

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P501 - Dispose of contents/container to an authorised waste collection point

Supplemental Hazard information (EU)

EUH205 - Contains epoxy constituents. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

2.3 Other hazards

- Not a PBT according to REACH Annex XIII
- Substance not identified as having endocrine disrupting properties

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

	CAS Number	EC Number	REACH Registration Number	Categories	H Statements	Concentration
Aluminum Hydroxide	21645-51-2	244-492-7	01-2119529246-39-0000	Substance with a work place exposure limit	None	50 - 70%
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	216-823-5	01-2119456619-26-0000	Skin Irrit. 2 Skin Sens. 1 Eye Irrit. 2 Aquatic Chronic 2	H315 H317 H319 H411	10 - 30%
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8	219-371-7	01-2119494060-45-0000	Acute Tox. 4 Skin Irrit. 2 Skin Sens. 1 Eye Irrit. 2 Acute Tox. 4	H312 H315 H317 H319 H332	10 - 30%
Calcined Kaolin	92704-41-1	296-473-8	Not applicable	Substance with a work place exposure limit	None	5 -10%
Silicones and siloxanes, dimethyl-, reaction products with silica	67762-90-7	924-588-1	Not applicable	Substance with a work place exposure limit	None	<1%
Carbon Black	1333-86-4	215-609-9	01-2119384822-32-0000	Substance with a work place exposure limit	None	<0.5%

SECTION 4: First aid measures**4.1 General**

- Use personal protective equipment as required.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

SECTION 4: First aid measures (....)

- Wash contaminated clothing before reuse.

Contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Contact with skin

After contact with skin, wash immediately with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention.

Ingestion

If swallowed, rinse mouth with water (only if the person is conscious)

Give water or milk to drink

Do NOT induce vomiting.

Get medical advice/attention if you feel unwell.

Inhalation

Remove patient to fresh air

Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

- In cases of severe exposure, allergic reaction in susceptible people may develop
- In cases of severe exposure, redness and irritation may develop

4.3 Indication of any immediate medical attention and special treatment needed

- Treat symptomatically
-

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide

5.2 Special hazards arising from the substance or mixture

- Decomposition products may include toxic and irritant fumes
- Decomposition products may include carbon oxides

5.3 Advice for firefighters

- Keep container(s) exposed to fire cool, by spraying with water
 - Prevent run off water from entering drains if possible
 - Wear Positive-Pressure Breathing Apparatus
-

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Wear protective clothing as per section 8
- Wash thoroughly after dealing with spillage
- Avoid contact with skin and eyes

6.2 Environmental precautions

- Avoid release to the environment.
-

SECTION 6: Accidental release measures (....)

- Absorb spillage in suitable inert material
- Do not discharge into drains or the environment, dispose to an authorised waste collection point

6.3 Methods and material for containment and cleaning up

- Wear protective clothing as per section 8
- Absorb spillage in suitable inert material
- Do not discharge into drains or the environment, dispose to an authorised waste collection point
- Wash thoroughly after dealing with spillage
- Collect spillage.

6.4 Reference to other sections

- Wear protective clothing as per section 8
 - See Section 11 - Toxicological Information
-

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Avoid release to the environment.
- Wear protective clothing as per section 8
- Take off contaminated clothing and wash it before reuse.
- In cases of severe exposure, allergic reaction in susceptible people may develop
- Do not eat, drink or smoke when using this product.
- After contact with skin, wash immediately with plenty of soap and water
- Wash hands and working surfaces thoroughly after handling.
- Use good personal hygiene practices
- Wash contaminated clothing before reuse.
- Dispose of contents/container to an authorised waste collection point

7.2 Conditions for safe storage, including any incompatibilities

- Keep container tightly closed, in a cool, well ventilated place
- Keep cool. Protect from sunlight.
- Keep away from food, drink and animal feedingstuffs
- Product may crystallise or separate if exposed to cold temperatures for extended periods of time. If this occurs, the product should be warmed to 38-60°C for one hour. If the product is in a bulk form stir until clear.

7.3 Specific end use(s)

- See Section 1.2
-

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Aluminum Hydroxide**

WEL (inhalable dust): 2.5 mg/m³ (PL), 10 mg/m³ (UK)
WEL (respirable dust): 1.2 mg/m³ (PL), 4 mg/m³ (UK)
WEL: 3 mg/m³ (CH)

bis-[4-(2,3-epoxipropoxy)phenyl]propane

DNEL (Industry; inhalational, long term systemic effects): 4.93 mg/m³
DNEL (Industry; dermal, long term systemic effects): 0.75 mg/kg bw/day
DNEL (Consumer; inhalational, long term systemic effects): 0.87 mg/m³

SECTION 8: Exposure controls/personal protection (....)

DNEL (Consumer; dermal, long term systemic effects): 0.0893 mg/kg bw/day

DNEL (Consumer; oral, long term systemic effects): 0.5 mg/kg bw/day

1,4-bis(2,3 epoxypropoxy)butane

DNEL (Consumer; inhalational, long term systemic effects): 1.16 mg/m³

DNEL (Consumer; oral, long term systemic effects): 0.33 mg/kg bw/day

DNEL (Consumer; dermal, long term systemic effects): 3.33 mg/kg bw/day

DNEL (Industry; dermal, long term systemic effects): 6.66 mg/kg bw/day

DNEL (Industry; inhalational, long term systemic effects): 4.7 mg/m³

Calcined Kaolin

WEL (respirable dust): 2 mg/m³ (8 hour TWA)

Silicones and siloxanes, dimethyl-, reaction products with silica

WEL (inhalable dust) (long term): 6 mg/m³ (UK)

WEL (respirable dust) (long term): 2.4 mg/m³ (UK)

Carbon Black

DNEL (Industry; inhalational, long term systemic effects): 1 mg/m³

DNEL (Consumer; inhalational, long term systemic effects): 0.06 mg/m³

WEL (inhalable dust): (TWA) 3 mg/m³ (BE), (TWA) 2 mg/m³ (CZ), (TWA) 3.5 mg/m³ (DK), (TWA) 3.5 mg/m³ (FI), (STEL) 7 mg/m³ (FI), (TWA) 3.5 mg/m³ (FR), (TWA) 3.5 mg/m³ (GR), (STEL) 7 mg/m³ (GR), (TWA) 3 mg/m³ (IE), (STEL) 15 mg/m³ (IE), (TWA) 3 mg/m³ (IT), (TWA) 3.5 mg/m³ (NO), (STEL) 7 mg/m³ (NO), (TWA) 4 mg/m³ (PL), (TWA) 3 mg/m³ (PT), (TWA) 2 mg/m³ (SK), (STEL) 10 mg/m³ (SK), (TWA) 3.5 mg/m³ (ES), (TWA) 3 mg/m³ (SE), (TWA) 3.5 mg/m³ (UK), (STEL) 7 mg/m³ (UK), (USA) TLV (TWA): 3 mg/m³

8.2 Exposure controls

- This Safety Data Sheet does not constitute a workplace risk assessment
- In case of inadequate ventilation wear respiratory protection.
- Eyewash bottles should be available
- Wear suitable protective clothing, eye/face protection and gloves
- Gloves should be chemical resistant and comply with an approved standard such as EN 455 or EN 374 and made from latex, nitrile or neoprene. Protective clothing should be based on the results of an exposure assessment. A polymer laminate apron is recommended in most cases. Eye and face protection should be chemical resistant and comply with an approved standard such as EN 166. If a respirator is needed following an exposure assessment it should conform to EN 136 or EN 143 (P3)
- Check with personal protection equipment manufacturer
- Use good personal hygiene practices
- Do not eat, drink or smoke when using this product.
- Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

SECTION 9: Physical and chemical properties (....)

- Appearance: Paste
- Colour: Black
- Odour: Characteristic odour
- Boiling Point/Range: >230°C
- Flammability: Flash point: >150 °C (CC)
- pH: Not available
- Solubility in water: Partly soluble in water
- Density: Density (water=1): 1.68

9.2 Other information

- No information available
-

SECTION 10: Stability and reactivity**10.1 Reactivity**

- Reference to other sections

10.2 Chemical stability

- Considered stable under normal conditions

10.3 Possibility of hazardous reactions

- No hazardous reactions known if used for its intended purpose

10.4 Conditions to avoid

- No hazard expected under normal conditions of use
- Keep away from heat
- Keep away from static electricity

10.5 Incompatible materials

- Strong oxidising agent
- Strong alkalis
- Strong acids
- Reacts with amines

10.6 Hazardous decomposition products

- No hazardous decomposition products known
-

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

- Estimated LD₅₀ (oral) (ATE) : >2000 mg/kg
- Estimated LD₅₀ (dermal) (ATE) : 10318.95 mg/kg
- Estimated LD₅₀ (inhalational) (ATE) : 103.1895 mg/l/4hr (gas/vapour)

Aluminum Hydroxide

LD₅₀ (oral, rat): >2,000 mg/kg

bis-[4-(2,3-epoxipropoxy)phenyl]propane

SECTION 11: Toxicological information (....)

LD₅₀ (oral, rat): >15,000 mg/kg

LD₅₀ (skin, rat): >23,000 mg/kg

1,4-bis(2,3 epoxypropoxy)butane

LD₅₀ (oral, rat): 1,410 mg/kg

Estimated LD₅₀ (dermal) (ATE) : 1,100 mg/kg

Estimated LD₅₀ (inhalational) (ATE) : 11 mg/l

Calcined Kaolin

LC₅₀ (inhalation, rat): >2.19 mg/l/4h

LD₅₀ (oral, rat): >5,000 mg/kg

LD₅₀ (skin, rat): >5,000 mg/kg

Silicones and siloxanes, dimethyl-, reaction products with silica

LD₅₀ (oral, rat): >5,000 mg/kg

LD₅₀ (skin, rat): >2,000 mg/kg

Carbon Black

LD₅₀ (oral, rat): >2,000 mg/kg

LD₅₀ (dermal, rabbit): >2,000 mg/kg

LC₅₀ (inhalation, rat): (4h) >4.6 mg/m³

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on the available data, the classification criteria are not met

Carcinogenicity

Based on the available data, the classification criteria are not met

Reproductive toxicity

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - single exposure

Based on the available data, the classification criteria are not met

STOT (specific target organ toxicity) - repeated exposure

Based on the available data, the classification criteria are not met

SECTION 11: Toxicological information (....)**Aspiration hazard**

Based on the available data, the classification criteria are not met

11.2 Information on other hazards

- No information available

SECTION 12: Ecological information**12.1 Toxicity****Aluminum Hydroxide**

LC₅₀ (fish): >5,000 mg/l (96 hr)
Estimated Value

bis-[4-(2,3-epoxypropoxy)phenyl]propane

EC₅₀ (Daphnia magna): 1.8 mg/l (48 hr)
LC₅₀ (fish): 2 mg/l (96 hr)
PNEC (Fresh water): 0.006 mg/l
PNEC (intermittent): 0.018 mg/l
PNEC (Marine water): 0.0006 mg/l
PNEC (Sediment; fresh water): 0.341 mg/kg
PNEC (Sediment; marine water): 0.0341 mg/kg
PNEC (Soil): 0.0647 mg/kg
PNEC (STP): 10 mg/l

1,4-bis(2,3 epoxypropoxy)butane

EC₅₀ (Daphnia magna): 75 mg/l (48 hr)
IC₅₀ (algae): >160 mg/l (72 hr)
LC₅₀ (fish): 19.8 mg/l (96 hr)
PNEC (Sediment; marine water): 0.008 mg/kg
PNEC (Marine water): 0.002 mg/l
PNEC (Soil): 0.003 mg/kg
PNEC (STP): 100 mg/l
PNEC (Sediment; fresh water): 0.084 mg/kg
PNEC (Fresh water): 0.024 mg/l

Calcined Kaolin

IC₅₀ (algae): >1,000 mg/l (72 hr)
EC₅₀ (daphnia): >700 mg/l (48 hr)
LC₅₀ (fish): >1,000 mg/l (96 hr)

Silicones and siloxanes, dimethyl-, reaction products with silica

EC₅₀ (daphnia): >1,000 mg/l (48 hr)

SECTION 12: Ecological information (....)

LC₅₀ (fish): >10,000 mg/l (96 hr)

Carbon Black

EC₅₀ (daphnia): >1,000 mg/l (48 hr)

LC₅₀ (fish): >1,000 mg/l (96 hr)

PNEC (Fresh water): 50 mg/l

12.2 Persistence and degradability

- Not readily biodegradable

12.3 Bioaccumulative potential

- Bioaccumulation is insignificant

12.4 Mobility in soil

- partly miscible with water

12.5 Results of PBT and vPvB assessment

- Not a PBT according to REACH Annex XIII

12.6 Endocrine disrupting properties

- Substance not identified as having endocrine disrupting properties

12.7 Other adverse effects

- No information available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
- Wear protective clothing as per section 8
- Dispose of contents/container to an authorised waste collection point

SECTION 14: Transport information**14.1 UN number or ID number**

- UN No.: 3082

14.2 UN proper shipping name

- Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxy)phenyl]propane)

14.3 Transport hazard class(es)

- Hazard Class: 9

14.4 Packing group

- Packing Group: III

14.5 Environmental hazards

- Marine Pollutant

SECTION 14: Transport information (....)

- Environmentally hazardous

14.6 Special precautions for user

- IMDG EmS: F-A, S-F
- Tunnel Code: (E)
- Emergency Action Code: 3Z

14.7 Maritime transport in bulk according to IMO instruments

- Not applicable

14.8 Transport Regulations

- Special Provisions Apply: (IATA: A197), (ADR: 375) These substances when transported in single or combination packages containing a net quantity per single or inner packaging of 5L or less for liquids or having a net weight per single or inner packaging of 5KG or less for solids, are not subject to any other provisions of these regulations provided the packages meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8
-

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- This Safety Data Sheet is provided in compliance with the Health and Safety at Work Act
- This Safety Data Sheet is provided in compliance with the EC Regulations 1907/2006, 1272/2008, 2015/830 and 2020/878

15.2 Chemical safety assessment

- This product is either exempt from REACH or does not meet the minimum volume threshold for a chemical safety assessment (CSA)
-

SECTION 16: Other information

Text not given with phrase codes where they are used elsewhere in this safety data sheet:- H312: Harmful in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H332: Harmful if inhaled. H411: Toxic to aquatic life with long lasting effects.

Sections updated: 1.1, 8.2, 14.8

This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own use.