
Technical Data

RT110BK

Fast Setting Epoxy Adhesive

Description

RT110 is an easy spreading, fast setting epoxy adhesive, which bonds well to a wide range of materials.

Benefits

- Sets in minutes at room temperature
- Will bond metals, glass, wood, rubbers and many plastics
- Excellent general purpose adhesive
- Available in black for small volume potting of components
- Supplied in DuoSyringe for easy application
- Standard size is 50g, with associated mixing nozzles and dispenser guns

Typical Properties

Curing (*measurements at 23°C*)

Work life:	5 – 10 minutes
Time to handling:	15 minutes
Time to full cure:	2 hours

Bond Strength (*measurements at 23°C*)

Lap Shear (Al / Al):	20 MPa
Tensile Strength:	47 MPa

Colour

Milky white or black

Related Products

- RT111 fast setting structural epoxy adhesive
- RT112 non-sag, fast setting epoxy sealant
- RT125 flexible, high performance epoxy adhesive
- TriPatch wraparound epoxy repair system

Resintech Limited warrants only that it's products meet the specifications stated herein. Typical properties where stated are to be considered as representative of the current production and should not be treated as specifications. While the information presented is believed to be true and reliable, users are advised to conduct sufficient investigations to ensure the suitability of any product for it's intended use. Resintech Limited cannot accept any responsibility for loss or damage that may result from the use of this information.