

RT112



Fast Setting Epoxy Sealant

Description

RT112 is a non-sag, fast setting epoxy sealant, which bonds well to a wide range of materials.

Benefits

- Sets in minutes at room temperature
- Applied as a bead, will not sag even on a vertical surface
- Will bond metals, glass, wood, rubbers and many plastics
- Excellent for gap or crack filling
- Supplied in DuoSyringe for easy application
- 50ml and 200ml sizes available with associated mixing nozzles and dispenser guns

Typical Properties

Curing (measurements at 23°C)

Work life:	5 – 10 minutes
Time to handling:	15 minutes
Time to full cure:	2 hours

Bond Strength (measurements at 23°C)

Lap Shear (Al / Al)	20 MPa
Tensile Strength	47 MPa

Colour

Fairly clear as a film, milky white otherwise

Related Products

- RT110 fast setting epoxy adhesive
- RT111 fast setting epoxy adhesive
- RT125 flexible, high performance epoxy adhesive
- TriPatch wraparound epoxy repair system

Issue 3 - April 2005

Resintech Limited warrants only that its products meet the specifications stated herein. Typical properties where stated are to be considered as representative of the current production and should not be treated as specifications. While the information presented is believed to be true and reliable, users are advised to conduct sufficient investigations to ensure the suitability of any product for its intended use. Resintech Limited cannot accept any responsibility for loss or damage that may result from the use of this information.

Resintech Limited

Horcott Industrial Estate, Fairford, Gloucestershire, GL7 4BX, United Kingdom

t: +44 (0)1285 712755 f: +44 (0)1285 712999 e: technical@resintech.co.uk w: www.resintech.co.uk