

RT355



Fast Setting Flexible Epoxy Resin System

Description

RT355 is a fast cure, thixotropic epoxy resin system with good adhesion to flexible substrates.

Benefits

- Sets in minutes at room temperature
- Will bond metals, glass, wood, rubbers and many plastics
- Good shock resistance
- Good temperature and oil resistance
- Supplied in DuoSyringe for easy application
- Standard size is 50ml, with associated mixing nozzles and dispenser guns
- Suitable for applications of less than 25 grams

Typical Properties

Curing (measurements for 10g mass at 23°C)

Work life:	5 – 10 minutes
Time to handling:	20 minutes
Time to full cure:	2 hours

Typical Performance (measurements at 23°C)

Peel (Neoprene/Neoprene)	50N/25mm
Hardness (Shore A)	80
Operating temperature	-40°C to +150°C

Colour

Black

Related Products

- The Resintech range of potting epoxies
- RT125 flexible, high performance epoxy adhesive

Issue 5 - April 2005

Resintech Limited warrants only that its products meet the specifications stated herein. Typical properties where stated are to be considered as representative of the current production and should not be treated as specifications. While the information presented is believed to be true and reliable, users are advised to conduct sufficient investigations to ensure the suitability of any product for its intended use. Resintech Limited cannot accept any responsibility for loss or damage that may result from the use of this information.

Resintech Limited

Horcott Industrial Estate, Fairford, Gloucestershire, GL7 4BX, United Kingdom

t: +44 (0)1285 712755 f: +44 (0)1285 712999 e: technical@resintech.co.uk w: www.resintech.co.uk